



Texsal FV	2mm	APP modified-bitumen Waterproofing membrane With fibre-glass reinforcement	Weight 2.5kg/m2 Roll 1 x 13m	Non-trafficable flat roofs, warm roofs, In multi-layer system. High dimensional stability
Morterplas FPV Min	5Kg	Mineral finished, APP Modified Bitumen waterproofing Membrane with stabilised polyester reinforcement	Weight 5kg/m2 Roll 1 x 8m	Non-trafficable flat and pitched roofs, In single layer system
Morterplas SBS FV	2.4kg 2mm	SBS modified-bitumen Waterproofing membrane With fibre-glass reinforcement.	Weight 3kg/m2 Roll 1 x 13m	Trafficable and non-trafficable flat roofs, Warm & inverted roofs, in multi-layer system as a first layer. High dimensional stability
Morterplas SBS FPV Min	5kg 4mm	Mineral finished, SBS Modified Bitumen waterproofing Membrane with stabilised polyester reinforcement	Weight 5kg/m2 Roll 1 x 8m	Non-trafficable flat roofs, warm roofs, In multi-layer system.
Texself GS	2mm	Self-adhesive waterproofing Membrane with aluminium-polyethylene (AL+PE) Reinforcement composite finished with a polyethylene film on its upper side	Roll 1 x 15m	Methane and Radon gas barrier. Water vapour barrier.

